


Silicon Nitride (Si₃N₄) – CeramaSil-N™

PCSN2000








Material webpage



Overview

Silicon Nitride (Si₃N₄) has the most versatile combination of mechanical, thermal, and electrical properties of any advanced ceramic material. It is tough, strong, electrically insulating, and has exceptional thermal shock and impact resistance. PCSN2000 has enhanced strength due to hot pressing.

Primary Advantages

-  Highest Strength Si₃N₄ Grade
-  Good Fracture Toughness
-  Thermal Shock, Impact, & Wear Resistant
-  Lightweight – Low density
-  Electrically Insulating

Applications

- Aerospace Applications
- Chemical Plant Engineering
- Engine Wear Parts
- Foundry Applications
- Mechanical Engineering
- Medical Components

	Properties	Units	PCSN2000
Mechanical	Compressive Strength	MPa	3000
	Density	g/cm ³	3.18-3.40
	Flexural Strength @ 25°C	MPa	970
	Fracture Toughness K _{IC}	MPa m ^{1/2}	6.2
	Hardness	GPa	15
	Young's Modulus	GPa	300
	Poisson's Ratio	-	0.26
Thermal	Thermal Conductivity	W/mK	22
	CTE @ 25°C – 250°C	10 ⁻⁶ /K	1.4
	CTE @ 25°C – 1000°C	10 ⁻⁶ /K	3.2
	Thermal Shock Parameter R1	K	748
	Thermal Shock Parameter R2	W/m	17
	Maximum Temperature (Air)	°C	1200
	Maximum Temperature (Inert)	°C	1400
Electrical	Dielectric Constant @ 1 MHz	-	8
	Dielectric Strength @ 25°C	kV/mm	19
	Volume Resistivity @ 25°C	ohm-cm	10 ¹⁴

Disclaimer: The values presented are mean and typical of those resulted from test samples. They are provided as an indication only to serve as guidance in the design of ceramic components and are not guaranteed in any way. The actual values can vary according to the shape and size of the envisioned component.



PRECISION CERAMICS UK
uk@precision-ceramics.com
+44 (0)121 687 5858

PRECISION CERAMICS USA
info@precision-ceramics.com
+1 (727) 388 5060

PRECISION CERAMICS EU
eu@precision-ceramics.com
+353 51 550 480